

www.swellglobalcompany.com



Exceeding The Limits To Always Get The Best



CONNECTING THE VALUE OF SLAB





CONTINUA+ is the most efficient, highest-productivity technology for the accurately managed manufacture of porcelain slabs and tiles, also producible with traditional bodies. The slabs are, in fact, formed without using a traditional press or mould, ensuring maximum flexibility in terms of size and thickness.





CONTINUA+ seamlessly integrates the powder forming phase and subsequent digital decoration. The key strengths of this exclusive process are high quality texturing and unrivalled surface shine.



PRODUCT

Formats





The thicknesses are one of the most important elements characterizing..

15 mm is set aside for the most demanding product applications such as kitchen countertops.



EDGE Profiles


Double straight rounded edge

Rounded straight edge

Half bullnoss



Full bullnoss



Demi bullnoss




Micro bevel




Straight squared edge



Double straight squared edge



Rounded edge at 45°



Squared edge at 45°

Giving a nice trim to the edges of the tiles adds to its beauty. As these tiles are of the good thickness of 15mm, it is possible to shape its edges in different styles and create aesthetically rich countertops for your space.


JOINT POSSIBILITIES














The Functionality of The Residential Kitchen

for Today's Homeowi

eading Edge Design



PRODUCTRange



PRODUCT Finishes

FEEL

A matte finish with a light layer of enamel for subtle shine and a pleasantly soft touch Surface finish which is easy to clean.





APPLICATION

Areas

KITCHEN COUNTERTOP

LIGHTWEIGHT

DINING TABLE

MY

WATERPROOF

LIVING ROOM

RESISTANT TO SCRATCHES

TECHNICAL

Features

FURNITURE

J,

 \bigoplus

RESISTANT TO HIGH TEMPERATURES

STAIRCASE

EASY TO CLEAN

OFFICE TABLE

DOOR \WINDOW

RESISTANT TO BENDING

TABLE TOP

口

100% NATURAL

FRAME

O


RECYCLABLE

HYGIENIC

RESISTANT TO UV RAYS

FEEL






LOURENT GOLD

BODY

BLACK BODY

FINISH **Matt** SIZE **800**X**3000 MM**



MARQUINA NERO

BODY
BLACK BODY

FINISH **Matt** SIZE **800**X**3000 MM**



METAL BLACK

BODY
BLACK BODY


FINISH MATT SIZE **800**X**3000 MM**



PORTE NOIR

BODY
BLACK BODY

FINISH **Matt** SIZE **800**X**3000 MM**




WAVE BLACK

BLACK BODY

MATT

800X3000 MM




COCOA VENEER

BROWN BODY

MATT

800X3000 MM



NATURAL PINE DARK

BODY Brown Body

FINISH **Matt** SIZE **800**X**3000 MM**




SMOKE WALNUT

BODY
BROWN BODY

FINISH Matt


SIZE **800**X**3000 MM**



GREY BODY

MATT

800X3000 MM



GREY FLURRY

BODY GREY BODY FINISH MATT SIZE **800**X**3000 MM**




GREY ZINC

GREY BODY

MATT


800X3000 MM



VERSACE GOLD

BODY
GREY BODY

FINISH MATT SIZE **8003000 mm**




LIGHT VENEER

IVORY BODY

MATT


800X3000 MM



OAK NATURAL

BODY IVORY BODY

FINISH **Matt** SIZE **800**X**3000 MM**



NATURAL PINE LIGHT

ORANGE BODY

MATT


800X3000 MM



CEMENT FEEL

BODY
WALL STREET GREY BODY

FINISH MATT SIZE **800**X**3000 MM**




PIETRA GREY

WALL STREET GREY BODY

MATT


800X3000 MM



ARABESCATO GOLD

BODY WHITE BODY


FINISH Matt SIZE **800**X**3000 MM**



BIANCO EXTRA

BODY WHITE BODY


FINISH Matt SIZE **800**X**3000 MM**



WHITE BODY

MATT

800X3000 MM




BREACH

WHITE BODY

MATT


800X3000 MM



CALCATTA ULTRA

BODY WHITE BODY


FINISH Matt SIZE **800**X**3000 MM**



DELMARE

BODY WHITE BODY


FINISH **Matt** SIZE **800**X**3000 MM**



FURR WHITE

BODY WHITE BODY


FINISH **Matt** SIZE **800**X**3000 MM**




HEROZIN WHITE

BODY WHITE BODY

FINISH MATT SIZE **800**X**3000 MM**






WHITE BODY

MATT

800X3000 MM




MACHIA VECHIA

WHITE BODY

MATT


800X3000 MM



MONT BLANC

BODY WHITE BODY

FINISH **Matt** SIZE **800**X**3000 MM**




PEARL CREAM ONYX

WHITE BODY

MATT


800X3000 MM



STATUARIO ALTISSIMO

BODY WHITE BODY

FINISH Matt SIZE **800**X**3000 MM**



Cleaning & Maintenance

Our products are non porous (due to their high quality raw materials, stringent production parameters and state of the art technology), hence any dust or deposited waste cannot penetrate the surface.

For most cases only a damp cloth is sufficient for cleaning.

Regular cleaning highlights the aesthetic features of the surface and gives it exceptional shine.

For highly aggressive cleaning caused by some common food and substances follow the table below.

TYPE OF STAIN	CHEMICAL PRODUCT	EXAMPLE		
Grease	Alkaline - Solvent	Detergent Ammonia, Backing Soda		
Oil	Solvent Oxidant -	Alcohol, Liquid Bleach, Nail Paint Remover		
Ink	Solvent Acid Acid	Hydrochloric Acid, Vinegar, Red Harpic		
Rust	Acid Alkaline	Descaling Reagent, Hydro Chloric Acid		
Lime	Alkaline - Solvent	Hydro Chloric Acid Ammonia, Liquid		
Cement	Solvent Acid	Bleach Ammonia, Liquid Bleach Alcohol,		
Wine	Solvent Oxidant	Thinner Hydro Chloric Acid Alcohol,		
Coffee	Oxidant Alkaline	Thinner Liquid Bleach Liquid Bleach		
Rubber		Liquid Bleach		
Plaster				
Candle Wax				
lodine				
Blood				
Ice Cream				

Note: It is recommended that any kind of stain needs to get clean immediately / as soon as possible.

Technical Specification

CHARACTERISTIC	STANDARD AS PER ISO13006:2018/ EN14411 Gr.BIa	MEAN VALUE	TEST METHOD	
Regulatory Properties <u>Deviation in</u>				
Length and Width	± 0.30 % (±1.00mm)	± 0.10 % ± 5.00 % ±	ISO 10545-2 ISO	
Deviation in Thickness	± 5.00 % (±0.50mm)	0.10 % ± 0.10% ±	10545-2 ISO	
traightness in Side	± 0.30 % (±0.80mm)	0.50 % ± 0.50 % ±	10545-2 ISO	
Rectangularity	± 0.30 % (±1.50mm)	0.50 % >95%	10545-2 ISO	
Surface Flatness Central Curvature	± 0.40 % (±1.80mm)	defects free ΔE <	10545-2 ISO	
Surface Flatness Edge Curvature	± 0.40 % (±1.80mm)	0.30 Gloss Value>	10545-2 ISO	
Surface Flatness Warpage	± 0.40 % (±1.80mm)	90 3 <gloss< td=""><td>10545-2 ISO</td></gloss<>	10545-2 ISO	
urface Quality	>95% defects free	Value<7 7 <gloss< td=""><td>10545-2 ISO</td></gloss<>	10545-2 ISO	
Small Color Difference(for Plain Colour)	ΔE < 1.00 as per Value<18		10545-16 Gloss	
Glossiness (Polished)	mfg. as per mfg. as		Meter 60° Gloss	
Glossiness (Matt)	per mfg.		Meter 60° Gloss	
Glossiness (Satin/Posh)			Meter 60°	
Structural Properties Water absorption				
Bulk density Massive Mechanical	≤ 0.50 %	≤ 0.060 %	ISO 10545-3	
Properties Modulus of rupture Breaking	as per mfg.	Min. 2.28 g/cc	ISO 10545-3	
trength thickness <7.5 Breaking	45 poi 11119.	2.23 9, 33	100 100 10 0	
trength thickness ≥7.5 Breaking	Min. 35.0 N/mm ²	Min. 42.0 N/mm²	ISO 10545-4	
trength thickness ≥(175.5mm)	Min. 700.0 N	Min. 1000.0 N	ISO 10545-4	
Surface Mechanical Properties	Min. 1300.0 N	Min. 1800.0 N	ISO 10545-4	
MOH'S hardness #	Min. 1300.0 N	Min. 7500.0 N	ISO 10545-4	
Surface abrasion resistance #	MIII. 1300.0 N	MIII. 7300.0 N	130 10343-4	
Deep abrasion resistance #		Classia Miss (*/ Dasla Miss C	DC EN JEEE	
hermal Hydrometric Properties	as per mfg.	Glossy Min. 4*/ Posh Min. 6	BS EN 15771	
Moisture expansion	as per mfg.	Glossy Min. 2/ Posh Min. 3	ISO 10545-7	
hermal expansion(COE) at 100°C	Max.	Max. 132mm3	ISO 10545-6	
hermal shock resistance	175m3m		100 105/510	
mpact resistance(COR) #	Max. 0.06%(0.6mm/m)	Max. 0.02mm/m	ISO 10545-10	
Frost resistance	as per mfg.	Max. 6.0 x 1-06	ISO 10545-8	
Chemical Properties	Min. 10 Cycle	Min. ¹ 0 Cycle	ISO 10545-9	
Resistance to staining glazed	Min. 0.55	Min. 0.55	ISO 10545-5	
Resistance to household chemicals & swimming pool salts glazed	as per mfg.	Frost Proof	ISO 10545-12	
Resistance to low concentrate acid and	Min. Class 3	Min. Class 4	ISO 10545-14	
alkalis glazed Resistance to high concentrate acid and	Min. Class GB	Min. Class GA	ISO 10545-13	
ilkalis glazed				
Safety Properties	as per mfg.	Min. Class GLB**	ISO 10545-13	
skid resistance(DCOF-DRY) ##			100 105 /5	
Slip resistance(DCOF)(R value) ##	as per mfg.	Min. Class GHB**	ISO 10545-13	
Fire resistance				
	as per mfg.	Glossy P0(<12) / Posh ≥P1(12-24)	BS 7976-2	
	as per mfg.	R9 to R ¹³	DIN 51130	
	as per mfg.	Fire Proof	N.A.	
	as per mig.	FIIE PIOOI	1 V./~.	

Packing Details

PRODUCT	BODY	SIZE	THICKNESS	TILES / BOX	COVERAGE AREA / BOX	WEIGHT (Kgs)
Matt	Color Body	800x3000mm	15mm	1рс	25.83 Sq ft	84 Kgs

^{*}With Nano polished

** Except Hydrofluoric Acid & it's compound

Tiles Intended for use on floor

As per customer requirement